



Mono MEGA 106 Deck

TABELLA PORTATE

Spessore nominale Supporto Acciaio (mm)	Larghezza efficace appoggio: 100 mm 													
	l=cm	200	250	300	325	350	375	400	425	450	475	500	525	550
0,50	P = kg/m ²	290	180	115	95	80	70	60	50					
0,60		420	260	175	145	125	105	90	75	65	55			
0,70		525	330	220	185	160	135	115	100	85	70	55		
0,80		680	425	290	245	205	175	155	130	105	85	70	60	
1,00		920	580	395	335	285	245	210	175	145	115	95	80	65

Spessore nominale Supporto Alluminio (mm)	Larghezza efficace appoggio: 100 mm 													
	l=cm	200	250	300	325	350	375	400	425	450	475	500	525	550
0,60	P = kg/m ²	230	140	85	65									
0,70		290	175	105	80	60								
0,80		355	220	130	95	70	55							
1,00		490	305	170	125	95	75	55						

Spessore Pannello (mm)	Spessore Nominale Supporto Acciaio (mm)				
	0,50	0,60	0,70	0,80	1,00
	Peso Pannello (kg/m ²)				
50	8,4	9,6	10,8	12,0	14,3
60	8,8	10,0	11,2	12,4	14,7
80	9,6	10,8	12,0	13,2	15,5
100	10,4	11,6	12,8	14,0	16,3

Spessore Pannello (mm)	Spessore Nominale Supporto Alluminio (mm)			
	0,60	0,70	0,80	1,00
	Peso Pannello (kg/m ²)			
50	5,3	5,7	6,1	7,0
60	5,7	6,1	6,5	7,4
80	6,5	6,9	7,3	8,2
100	7,3	7,7	8,1	9,0

- Valori in Nero: Stati Limite Ultimo
- Valori in Rosso: Stati Limite di Esercizio (freccia = 1/200 Luce)

- Values in Black: Ultimate Limit States
- Values in Red: Serviceability Limit States (deflection = 1/200 span)